



SECUREX DIAMOND EXPANDED METAL FENCE SYSTEM

Type 1 – New Fence

Basic Installation Specifications

12' High – 4 rail system

Mesh Specification – ¾" - #9R, ¾" - #9F, 1-1/2" - #9R, 2" - #9R

Fence Framework – 4" OD SS40 line posts set a maximum of 93" O.C. Each post will have a 4" pressed steel dome cap to seal out moisture. The expanded metal fence system includes four horizontal line rails (top, bottom and 2 mid rails, minimum). Line rails consist of 1-5/8" x 13/16" x 14 ga steel channel installed using Securex bands with 1" square washers. Fence top and bottom rail is to be installed 3-8" from top or bottom edge of mesh and should be equal. Mid rails are installed evenly spaced between top and bottom rails.

Fence Terminal Posts (end and corner) – 4" or 6-5/8" OD SS40 posts will attach to remaining fence framework with Securex bands. Additionally, mesh will attach to terminal posts with 2 (total of 6) Securex end tensioners spaced evenly between rails at a max of 18" from rail. Corner posts will attach to line rails with Securex bands. Terminal posts will have matching pressed steel dome cap. Expanded metal mesh will fit flush to fence post or overlap max of 2" to eliminate open space.

Securex Expanded Metal Mesh – Galvanized expanded metal mesh material will be zinc coated hot dip galvanized per ASTM A123. If color coated mesh is required coating will meet specifications per ASTM 1043-06. Expanded metal mesh will overlap up to 3 diamonds or 3 inches (depending on diamond size) at fence line post, except where adjustment is needed to follow contour of terrain. Expanded metal mesh shall be installed flush and/or overlap the fence end post a maximum of 2". Expanded metal mesh panels shall have no more than 1" space between bottom of mesh and grade.

Fence Fittings – Mesh is connected to line post framework using 4" Securex c-clamps and Securex bar clamps. Install 2 (6 total) c-clamps evenly spaced between the four line rails at a max of 18" along line post. Expanded metal mesh is attached to line rails using Securex latch clamps and u-washers through the slotted channel rails at a max of 18" per panel (approx. 6 per rail). Securex latch clamps are also added at each end tensioner assembly point. Mesh is connected to terminal posts with Securex end tensioners, latch clamps and u-washers. If, due to terrain or spacing requirements, mesh overlaps at a position that does not coincide with a line post, mesh is joined using Securex bar clamps vertically positioned and evenly spaced.

Fence Fasteners/Bolts- The Securex expanded metal fence system recommends the use of stainless steel square shoulder carriage bolts with stainless steel breakaway nuts. Alternatively, the Securex system can be installed with standard carriage bolts tightened securely then peened to prevent removal.