



**SECUREX SAFETY RAIL – 42” HIGH
PARTIAL FILL PANEL
(available in steel or aluminum)**

Mesh size options:	67”w x 15”h with u-edging 67’w x 16”h with u-edging
Mesh panels per section:	2
Number of Rails:	3
Fittings (per section):	Iron Casting – Kee Safety Fittings meeting ASTM A47-77-32510
Post Height:	42”
Maximum Span:	72”
Framework Options:	Posts: 1-5/8” (1.660 OD) WT/SS40 round framework Posts: 2” (1.900 OD) WT/SS40 round framework
Fasteners:	Hardened steel hexagon set screws
Color Options Framework:	Hot Dip Galvanized to meet ASTM A123 Powder Coat - Safety Yellow, Black, Green
Expanded Metal Infill:	Hot Dip Galvanized to meet ASTM A123 Powder Coat – Safety Yellow, Black, Green
Expanded Metal Infill Style Designations:	1/2-#13R 3/4-#9R 3/4-#9F 1 1/2-#9R 2-#9R
Accessories Available:	Toeboards - OSHA 1910.23 ADA Compliant Handrail Shelving

Notes:
All Securex systems assume reverse diamond orientation unless otherwise requested.
Mesh panel size and configuration can be adjusted to design requirements.